

| MOBILUX COOLER |

INDEPENDENT OF POWER SUPPLY



TRICYCLE

FEATURES

- Low service costs
- Long life
- Graphics (option)

	MOBILUX COOLER11	MOBILUX COOLER21
Climate class 4	4	4
Ambient temperature (Celsius)	+16 to +30	+16 to +30
Climate class 5	5	5
Ambient temperature (Celsius)	+16 to +43	+16 to +43
Gross volume, litres	130	227
Net volume, litres	117	206
Temperature range inside unit	+4 to +8	+4 to +8
Energy consumption/ 24 h (R134a) climate class 4 (kwh) 60 % running time	0,87	n/a
Input power for R134a (watt)	60	n/a
DIMENSIONS		
External dimensions (wxdxh)	720*650*865	1050*650*865
Internal dimensions (wxdxh)	520*450*650	850*450*650
Dimension A	720	1050
Dimension B	650	650
Dimension C	865	865
Dimension D	780	780
Dimension E	520	850
Dimension F	320	650
Dimension G	450	450
Dimension H	650	650
Dimension J	400	400
Dimension L	850	850
Insulation(mm)	100	100
ACCESSORIES		
Dividers	Optional	Optional
Max. number of baskets (option)	1	2
Castors	Incl.	Incl.
Castors w. brakes	Optional	Optional
Lock	Optional	Optional
Thermometer	Optional	Optional
Internal light	n/a	n/a
OTHER DATA		
Outer cabinet	White	White
Inner cabinet	Aluminium	Aluminium
Graphics	Optional	Optional
Type of cooling	Static	Static
Type of drain	Manual	Manual
Power	220V/50Hz	220V/50Hz
Power 110volt / 60 hz	Optional	Optional
Thermostat	Mechanical	Mechanical
Net weight, kg	56	69
Gross weight, kg	62	75
SHIPPING		
20' cont. Capacity	42	30
40' cont. Capacity	90	64
Standard Trailer capacity	102	74